

---

# **django-import-export Documentation**

*Release 2.0.2*

**Bojan Mihelac**

**Feb 20, 2020**



<b>1</b>	<b>Installation and configuration</b>	<b>3</b>
1.1	Settings . . . . .	3
1.2	Example app . . . . .	4
<b>2</b>	<b>Getting started</b>	<b>5</b>
2.1	Creating import-export resource . . . . .	6
2.2	Exporting data . . . . .	6
2.3	Customize resource options . . . . .	6
2.4	Declaring fields . . . . .	7
2.5	Advanced data manipulation on export . . . . .	8
2.6	Customize widgets . . . . .	8
2.7	Importing data . . . . .	9
2.8	Signals . . . . .	9
2.9	Admin integration . . . . .	10
<b>3</b>	<b>Import data workflow</b>	<b>15</b>
3.1	Transaction support . . . . .	16
<b>4</b>	<b>Changelog</b>	<b>17</b>
4.1	2.0.2 (2020-02-16) . . . . .	17
4.2	2.0.1 (2020-01-15) . . . . .	17
4.3	2.0 (2019-12-03) . . . . .	17
4.4	1.2.0 (2019-01-10) . . . . .	19
4.5	1.1.0 (2018-10-02) . . . . .	19
4.6	1.0.1 (2018-05-17) . . . . .	19
4.7	1.0.0 (2018-02-13) . . . . .	20
4.8	0.7.0 (2018-01-17) . . . . .	20
4.9	0.6.1 (2017-12-04) . . . . .	20
4.10	0.6.0 (2017-11-23) . . . . .	20
4.11	0.5.1 (2016-09-29) . . . . .	21
4.12	0.5.0 (2016-09-01) . . . . .	21
4.13	0.4.5 (2016-04-06) . . . . .	22
4.14	0.4.4 (2016-03-22) . . . . .	22
4.15	0.4.3 (2016-03-08) . . . . .	22
4.16	0.4.2 (2015-12-18) . . . . .	22
4.17	0.4.1 (2015-12-11) . . . . .	22
4.18	0.4.0 (2015-12-02) . . . . .	23

4.19	0.3.1 (2015-11-20)	23
4.20	0.3 (2015-11-20)	23
4.21	0.2.9 (2015-11-12)	23
4.22	0.2.8 (2015-07-29)	23
4.23	0.2.7 (2015-05-04)	23
4.24	0.2.6 (2014-10-09)	24
4.25	0.2.5 (2014-10-04)	24
4.26	0.2.4 (2014-09-18)	24
4.27	0.2.3 (2014-07-01)	24
4.28	0.2.2 (2014-04-18)	24
4.29	0.2.1 (2014-02-20)	24
4.30	0.2.0 (2014-01-30)	25
4.31	0.1.6 (2014-01-21)	25
4.32	0.1.5 (2013-11-29)	25
4.33	0.1.4	25
4.34	0.1.3	25
4.35	0.1.2	25
4.36	0.1.1	25
4.37	0.1.0	26
<b>5</b>	<b>Admin</b>	<b>27</b>
<b>6</b>	<b>Resources</b>	<b>31</b>
6.1	Resource	31
6.2	ModelResource	33
6.3	ResourceOptions (Meta)	34
6.4	modelresource_factory	35
<b>7</b>	<b>Widgets</b>	<b>37</b>
<b>8</b>	<b>Fields</b>	<b>43</b>
<b>9</b>	<b>Instance loaders</b>	<b>45</b>
<b>10</b>	<b>Temporary storages</b>	<b>47</b>
10.1	TempFolderStorage	47
10.2	CacheStorage	47
10.3	MediaStorage	47
<b>11</b>	<b>Results</b>	<b>49</b>
11.1	Result	49
<b>12</b>	<b>Forms</b>	<b>51</b>
	<b>Python Module Index</b>	<b>53</b>
	<b>Index</b>	<b>55</b>

django-import-export is a Django application and library for importing and exporting data with included admin integration.

**Features:**

- support multiple formats (Excel, CSV, JSON, ... and everything else that `tablib` supports)
- admin integration for importing
- preview import changes
- admin integration for exporting
- export data respecting admin filters




Fig. 1: A screenshot of the change view with Import and Export buttons.



---

## Installation and configuration

---

django-import-export is available on the Python Package Index (PyPI), so it can be installed with standard Python tools like `pip` or `easy_install`:

```
$ pip install django-import-export
```

This will automatically install many formats supported by `tablib`. If you need additional formats like `cli` or `Pandas DataFrame`, you should install the appropriate `tablib` dependencies (e.g. `pip install tablib[pandas]`). Read more on the [‘tablib format documentation page’](#).

Alternatively, you can install the git repository directly to obtain the development version:

```
$ pip install -e git+https://github.com/django-import-export/django-import-export.git  
↪#egg=django-import-export
```

Now, you’re good to go, unless you want to use `django-import-export` from the admin as well. In this case, you need to add it to your `INSTALLED_APPS` and let Django collect its static files.

```
# settings.py  
INSTALLED_APPS = (  
    ...  
    'import_export',  
)
```

```
$ python manage.py collectstatic
```

All prerequisites are set up! See *Getting started* to learn how to use `django-import-export` in your project.

## 1.1 Settings

You can use the following directives in your settings file:

**IMPORT\_EXPORT\_USE\_TRANSACTIONS** Global setting controls if resource importing should use database transactions. Default is `False`.

**IMPORT\_EXPORT\_SKIP\_ADMIN\_LOG** Global setting controls if creating log entries for the admin changelist should be skipped when importing resource. The *skip\_admin\_log* attribute of *ImportMixin* is checked first, which defaults to `None`. If not found, this global option is used. This will speed up importing large datasets, but will lose changing logs in the admin changelist view. Default is `False`.

**IMPORT\_EXPORT\_TMP\_STORAGE\_CLASS** Global setting for the class to use to handle temporary storage of the uploaded file when importing from the admin using an *ImportMixin*. The *tmp\_storage\_class* attribute of *ImportMixin* is checked first, which defaults to `None`. If not found, this global option is used. Default is `TempFolderStorage`.

**IMPORT\_EXPORT\_IMPORT\_PERMISSION\_CODE** Global setting for defining user permission that is required for users/groups to execute import action. Django builtin permissions are `change`, `add`, and `delete`. It is possible to add your own permission code. Default is `None` which means everybody can execute import action.

**IMPORT\_EXPORT\_EXPORT\_PERMISSION\_CODE** Global setting for defining user permission that is required for users/groups to execute export action. Django builtin permissions are `change`, `add`, and `delete`. It is possible to add your own permission code. Default is `None` which means everybody can execute export action.

## 1.2 Example app

There's an example application that showcases what django-import-export can do. You can run it via:

```
cd tests
./manage.py runserver
```

Username and password for admin are `admin` and `password`.



## CHAPTER 2

---

### Getting started

---

For example purposes, we'll use a simplified book app. Here is our `models.py`:

```
# app/models.py

class Author(models.Model):
    name = models.CharField(max_length=100)

    def __str__(self):
        return self.name

class Category(models.Model):
    name = models.CharField(max_length=100)

    def __str__(self):
        return self.name

class Book(models.Model):
    name = models.CharField('Book name', max_length=100)
    author = models.ForeignKey(Author, blank=True, null=True)
    author_email = models.EmailField('Author email', max_length=75, blank=True)
    imported = models.BooleanField(default=False)
    published = models.DateField('Published', blank=True, null=True)
    price = models.DecimalField(max_digits=10, decimal_places=2, null=True,
↪blank=True)
    categories = models.ManyToManyField(Category, blank=True)

    def __str__(self):
        return self.name
```

## 2.1 Creating import-export resource

To integrate *django-import-export* with our `Book` model, we will create a `ModelResource` class in `admin.py` that will describe how this resource can be imported or exported:

```
# app/admin.py

from import_export import resources
from core.models import Book

class BookResource(resources.ModelResource):

    class Meta:
        model = Book
```

## 2.2 Exporting data

Now that we have defined a `ModelResource` class, we can export books:

```
>>> from app.admin import BookResource
>>> dataset = BookResource().export()
>>> print(dataset.csv)
id,name,author,author_email,imported,published,price,categories
2,Some book,1,,0,2012-12-05,8.85,1
```

## 2.3 Customize resource options

By default `ModelResource` introspects model fields and creates `Field`-attributes with an appropriate `Widget` for each field.

To affect which model fields will be included in an import-export resource, use the `fields` option to whitelist fields:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        fields = ('id', 'name', 'price',)
```

Or the `exclude` option to blacklist fields:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        exclude = ('imported', )
```

An explicit order for exporting fields can be set using the `export_order` option:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
```

(continues on next page)

(continued from previous page)

```
fields = ('id', 'name', 'author', 'price',)
export_order = ('id', 'price', 'author', 'name')
```

The default field for object identification is `id`, you can optionally set which fields are used as the `id` when importing:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        import_id_fields = ('isbn',)
        fields = ('isbn', 'name', 'author', 'price',)
```

When defining *ModelResource* fields it is possible to follow model relationships:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        fields = ('author__name',)
```

**Note:** Following relationship fields sets `field` as `readonly`, meaning this field will be skipped when importing data.

By default all records will be imported, even if no changes are detected. This can be changed setting the `skip_unchanged` option. Also, the `report_skipped` option controls whether skipped records appear in the import `Result` object, and if using the admin whether skipped records will show in the import preview page:

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        skip_unchanged = True
        report_skipped = False
        fields = ('id', 'name', 'price',)
```

See also:

*Resources*

## 2.4 Declaring fields

It is possible to override a resource field to change some of its options:

```
from import_export.fields import Field

class BookResource(resources.ModelResource):
    published = Field(attribute='published', column_name='published_date')

    class Meta:
        model = Book
```

Other fields that don't exist in the target model may be added:

```
from import_export.fields import Field

class BookResource(resources.ModelResource):
    myfield = Field(column_name='myfield')

    class Meta:
        model = Book
```

**See also:**

*Fields* Available field types and options.

## 2.5 Advanced data manipulation on export

Not all data can be easily extracted from an object/model attribute. In order to turn complicated data model into a (generally simpler) processed data structure on export, `dehydrate_<fieldname>` method should be defined:

```
from import_export.fields import Field

class BookResource(resources.ModelResource):
    full_title = Field()

    class Meta:
        model = Book

    def dehydrate_full_title(self, book):
        return '%s by %s' % (book.name, book.author.name)
```

In this case, the export looks like this:

```
>>> from app.admin import BookResource
>>> dataset = BookResource().export()
>>> print(dataset.csv)
full_title,id,name,author,author_email,imported,published,price,categories
Some book by 1,2,Some book,1,,0,2012-12-05,8.85,1
```

## 2.6 Customize widgets

A *ModelResource* creates a field with a default widget for a given field type. If the widget should be initialized with different arguments, set the `widgets` dict.

In this example widget, the `published` field is overridden to use a different date format. This format will be used both for importing and exporting resource.

```
class BookResource(resources.ModelResource):

    class Meta:
        model = Book
        widgets = {
            'published': {'format': '%d.%m.%Y'},
        }
```

**See also:**

*Widgets* available widget types and options.

## 2.7 Importing data

Let's import some data!

```

1 >>> import tablib
2 >>> from import_export import resources
3 >>> from core.models import Book
4 >>> book_resource = resources.modelresource_factory(model=Book)()
5 >>> dataset = tablib.Dataset(['', 'New book'], headers=['id', 'name'])
6 >>> result = book_resource.import_data(dataset, dry_run=True)
7 >>> print(result.has_errors())
8 False
9 >>> result = book_resource.import_data(dataset, dry_run=False)

```

In the fourth line we use `modelresource_factory()` to create a default `ModelResource`. The `ModelResource` class created this way is equal to the one shown in the example in section *Creating import-export resource*.

In fifth line a `Dataset` with columns `id` and `name`, and one book entry, are created. A field for a primary key field (in this case, `id`) always needs to be present.

In the rest of the code we first pretend to import data using `import_data()` and `dry_run` set, then check for any errors and actually import data this time.

**See also:**

*Import data workflow* for a detailed description of the import workflow and its customization options.

### 2.7.1 Deleting data

To delete objects during import, implement the `for_delete()` method on your `Resource` class.

The following is an example resource which expects a `delete` field in the dataset. An import using this resource will delete model instances for rows that have their column `delete` set to 1:

```

class BookResource(resources.ModelResource):
    delete = fields.Field(widget=widgets.BooleanWidget())

    def for_delete(self, row, instance):
        return self.fields['delete'].clean(row)

    class Meta:
        model = Book

```

## 2.8 Signals

To hook in the import export workflow, you can connect to `post_import`, `post_export` signals:

```

from django.dispatch import receiver
from import_export.signals import post_import, post_export

@receiver(post_import, dispatch_uid='balabala...')

```

(continues on next page)

(continued from previous page)

```
def _post_import(model, **kwargs):
    # model is the actual model instance which after import
    pass

@receiver(post_export, dispatch_uid='balabala...')
def _post_export(model, **kwargs):
    # model is the actual model instance which after export
    pass
```

## 2.9 Admin integration

### 2.9.1 Exporting

#### Exporting via list filters

Admin integration is achieved by subclassing `ImportExportModelAdmin` or one of the available mixins (`ImportMixin`, `ExportMixin`, `ImportExportMixin`):

```
# app/admin.py
from .models import Book
from import_export.admin import ImportExportModelAdmin

class BookAdmin(ImportExportModelAdmin):
    resource_class = BookResource

admin.site.register(Book, BookAdmin)
```




Fig. 1: A screenshot of the change view with Import and Export buttons.

#### Exporting via admin action

Another approach to exporting data is by subclassing `ImportExportActionModelAdmin` which implements export as an admin action. As a result it's possible to export a list of objects selected on the change list page:

Django administration WELCOME, ADMIN [VIEW SITE](#) / [CHANGE PASSWORD](#) / [LOG OUT](#)

Home > Core > Books > Import

## Import

This importer will import the following fields: id, name, author, author\_email, imported, published, published\_time, price, categories

File to import:  No file chosen

Format:

Fig. 2: A screenshot of the import view.

Django administration WELCOME, ADMIN [VIEW SITE](#) / [CHANGE PASSWORD](#) / [LOG OUT](#)

Home > Core > Books > Import

## Import

Below is a preview of data to be imported. If you are satisfied with the results, click 'Confirm import'

**Preview**

	ID	NAME	AUTHOR	AUTHOR_EMAIL	IMPORTED	PUBLISHED	PUBLISHED_TIME	PRICE	CATEGORIES
Update	2	<a href="#">FooBar</a>	1		0			<u>9.99</u>	
Update	1	Foo			0				

Fig. 3: A screenshot of the confirm import view.

```
# app/admin.py
from import_export.admin import ImportExportActionModelAdmin

class BookAdmin(ImportExportActionModelAdmin):
    pass
```




Fig. 4: A screenshot of the change view with Import and Export as an admin action.

Note that to use the *ExportMixin* or *ExportActionMixin*, you must declare this mixin **before** *admin.ModelAdmin*:

```
# app/admin.py
from django.contrib import admin
from import_export.admin import ExportActionMixin

class BookAdmin(ExportActionMixin, admin.ModelAdmin):
    pass
```

Note that *ExportActionMixin* is declared first in the example above!

## 2.9.2 Importing

It is also possible to enable data import via standard Django admin interface. To do this subclass *ImportExportModelAdmin* or use one of the available mixins, i.e. *ImportMixin*, or *ImportExportMixin*. Customizations are, of course, possible.

### Customize admin import forms

It is possible to modify default import forms used in the model admin. For example, to add an additional field in the import form, subclass and extend the *ImportForm* (note that you may want to also consider *ConfirmImportForm* as importing is a two-step process).

To use the customized form(s), overload *ImportMixin* respective methods, i.e. *get\_import\_form()*, and also *get\_confirm\_import\_form()* if need be.



For example, imagine you want to import books for a specific author. You can extend the import forms to include author field to select the author from.

Customize forms:

```
from django import forms

class CustomImportForm(ImportForm):
    author = forms.ModelChoiceField(
        queryset=Author.objects.all(),
        required=True)

class CustomConfirmImportForm(ConfirmImportForm):
    author = forms.ModelChoiceField(
        queryset=Author.objects.all(),
        required=True)
```

Customize ModelAdmin:

```
class CustomBookAdmin(ImportMixin, admin.ModelAdmin):
    resource_class = BookResource

    def get_import_form(self):
        return CustomImportForm

    def get_confirm_import_form(self):
        return CustomConfirmImportForm

    def get_form_kwargs(self, form, *args, **kwargs):
        # pass on `author` to the kwargs for the custom confirm form
        if isinstance(form, CustomImportForm):
            if form.is_valid():
                author = form.cleaned_data['author']
                kwargs.update({'author': author.id})
        return kwargs

admin.site.register(Book, CustomBookAdmin)
```

To further customize admin imports, consider modifying the following *ImportMixin* methods: *get\_form\_kwargs()*, *get\_import\_resource\_kwargs()*, *get\_import\_data\_kwargs()*.

Using the above methods it is possible to customize import form initialization as well as importing customizations.

**See also:**

*Admin* available mixins and options.



---

## Import data workflow

---

This document describes the import data workflow in detail, with hooks that enable customization of the import process. The central aspect of the import process is a resource's `import_data()` method which is explained below.

**import\_data** (*dataset*, *dry\_run=False*, *raise\_errors=False*)

The `import_data()` method of *Resource* is responsible for importing data from a given dataset.

*dataset* is required and expected to be a `tablib.Dataset` with a header row.

*dry\_run* is a Boolean which determines if changes to the database are made or if the import is only simulated. It defaults to `False`.

*raise\_errors* is a Boolean. If `True`, import should raise errors. The default is `False`, which means that eventual errors and traceback will be saved in `Result` instance.

This is what happens when the method is invoked:

1. First, a new `Result` instance, which holds errors and other information gathered during the import, is initialized.

Then, an `InstanceLoader` responsible for loading existing instances is initialized. A different `BaseInstanceLoader` can be specified via `ResourceOptions`'s `instance_loader_class` attribute. A `CachedInstanceLoader` can be used to reduce number of database queries. See the [source](#) for available implementations.

2. The `before_import()` hook is called. By implementing this method in your resource, you can customize the import process.

3. Each row of the to-be-imported dataset is processed according to the following steps:

#. The `before_import_row()` hook is called to allow for row data to be modified before it is imported

1. `get_or_init_instance()` is called with current `BaseInstanceLoader` and current row of the dataset, returning an object and a Boolean declaring if the object is newly created or not.

If no object can be found for the current row, `init_instance()` is invoked to initialize an object.

As always, you can override the implementation of `init_instance()` to customized how the new object is created (i.e. set default values).

2. `for_delete()` is called to determine if the passed `instance` should be deleted. In this case, the import process for the current row is stopped at this point.

3. If the instance was not deleted in the previous step, `import_obj()` is called with the `instance` as current object, `row` as current row and `dry_run`.

`import_field()` is called for each field in `Resource` skipping many- to-many fields. Many-to-many fields are skipped because they require instances to have a primary key and therefore assignment is postponed to when the object has already been saved.

`import_field()` in turn calls `save()`, if `Field.attribute` is set and `Field.column_name` exists in the given row.

4. It then is determined whether the newly imported object is different from the already present object and if therefore the given row should be skipped or not. This is handled by calling `skip_row()` with `original` as the original object and `instance` as the current object from the dataset.

If the current row is to be skipped, `row_result.import_type` is set to `IMPORT_TYPE_SKIP`.

5. If the current row is not to be skipped, `save_instance()` is called and actually saves the instance when `dry_run` is not set.

There are two hook methods (that by default do nothing) giving you the option to customize the import process:

- `before_save_instance()`
- `after_save_instance()`

Both methods receive `instance` and `dry_run` arguments.

6. `save_m2m()` is called to save many to many fields.

7. `RowResult` is assigned with a diff between the original and the imported object fields, as well as and `import_type` attribute which states whether the row is new, updated, skipped or deleted.

If an exception is raised during row processing and `import_data()` was invoked with `raise_errors=False` (which is the default) the particular traceback is appended to `RowResult` as well.

If either the row was not skipped or the `Resource` is configured to report skipped rows, the `RowResult` is appended to the `Result`

8. The `after_import_row()` hook is called

4. The `Result` is returned.

## 3.1 Transaction support

If transaction support is enabled, whole import process is wrapped inside transaction and rollbacked or committed respectively. All methods called from inside of `import_data(create / delete / update)` receive `False` for `dry_run` argument.

### 4.1 2.0.2 (2020-02-16)

- Add support for tablib  $\geq$  1.0 (#1061)
- Add ability to install a subset of tablib supported formats and save some automatic dependency installations (needs tablib  $\geq$  1.0)
- Use column\_name when checking row for fields (#1056)

### 4.2 2.0.1 (2020-01-15)

- Fix deprecated Django 3.0 function usage (#1054)
- Pin tablib version to not use new major version (#1063)
- Format field is always shown on Django 2.2 (#1007)

### 4.3 2.0 (2019-12-03)

- [django2.2] Add real support of Django 2.2 before 3.0 is out (#1021)
- fix: DateTimeWidget not timezone sensitive (#813) (#943)
- Move actions definition to ExportActionMixin (#992)
- Add language support: Turkish (#1013)
- Fix exception import for Django 3 (#1010)
- Fix potential header / row column mismatches for invalid rows in... (#995)
- Assume user is importing new data if id fields not included (#996)

- Fix bug with spaces in export filename, pass request and queryset (#980)
- Simplify Django version in TravisCI (#970)
- Merge pull request #966 from andrewgy8/bump-stale-bot-time
- Align error in rtl mode (#954)
- Add dutch translations (#951, #1024)
- Add 3.8-dev to travis ci (#926)
- Fix style in getting\_started docs (#952)
- Update documentation to show that mixins must be referenced before admin.ModelAdmin. (#946)
- JSONWidget updated with null value fix (#928)
- Import rows have background color (#929)
- Use resource get\_queryset in ModelInstanceLoader (#920)
- Simplify coerce to text type (#887)
- More flexibility in ConfirmImportForm, forms and resource kwargs (#893)
- Add JSON B type field mapping (#904)
- Scale back stale bot's time-to-stale (#918)
- test: explicitly order qs in ManyToManyWidget
- Add mysql to travis
- Expand doc strings to include Mixin superclasses (#914)
- Remove python2 compatibility decorator
- chore: fix Imports are incorrectly sorted.
- Use global env vars for postgres
- Used non-fixed id for test. Database is not torn down after each run, which means that the id is incrementing
- Fix warning from assertEquals
- Add psycopg2 as postgres driver to test requirements
- Add django version to the matrix
- Add matrix for sqlite and postgres testing
- Correct mistaken assertTrue() -> assertEquals()
- chore: add package long\_description
- chore: add python wheels to dev requirements (#890)
- Add github directory with PR and issue templates
- Isort all the things
- Use coveralls master branch tag in the readme
- Remove support for Django < 2.0 and Python < 3.5

## 4.4 1.2.0 (2019-01-10)

- feat: Better surfacing of validation errors in UI / optional model instance validation (#852)
- chore: Use modern setuptools in setup.py (#862)
- chore: Update URLs to use https:// (#863)
- chore: remove outdated workarounds
- chore: Run SQLite tests with in-memory database
- fix: Change logging level (#832)
- fix: Changed `get_instance()` return val (#842)

## 4.5 1.1.0 (2018-10-02)

- fix: Django2.1 ImportExportModelAdmin export (#797) (#819)
- setup: add django2.1 to test matrix
- JSONWidget for jsonb fields (#803)
- Add ExportActionMixin (#809)
- Add Import Export Permissioning #608 (#804)
- `write_to_tmp_storage()` for `import_action()` (#781)
- follow relationships on ForeignKeyWidget #798
- Update all pypi.python.org URLs to pypi.org
- added test for tsv import
- added unicode support for TSV for python 2
- Added ExportViewMixin (#692)

## 4.6 1.0.1 (2018-05-17)

- Make deep copy of fields from class attr to instance attr (#550)
- Fix #612: `NumberWidget.is_empty()` should strip the value if string type (#613)
- Fix #713: last day isn't included in results qs (#779)
- use Python3 compatible MySQL driver in development (#706)
- fix: warning U mode is deprecated in python 3 (#776)
- refactor: easier overriding widgets and default field (#769)
- Updated documentation regarding declaring fields (#735)
- custom js for action form also handles grappelli (#719)
- Use 'verbose\_name' in breadcrumbs to match Django default (#732)
- Add `Resource.get_diff_class()` (#745)
- Fix and add polish translation (#747)

- Restore raise\_errors to before\_import (#749)

## **4.7 1.0.0 (2018-02-13)**

- Switch to semver versioning (#687)
- Require Django>=1.8 (#685)
- upgrade tox configuration (#737)

## **4.8 0.7.0 (2018-01-17)**

- skip\_row override example (#702)
- Testing against Django 2.0 should not fail (#709)
- Refactor transaction handling (#690)
- Resolves #703 fields shadowed (#703)
- discourage installation as a zipped egg (#548)
- Fixed middleware settings in test app for Django 2.x (#696)

## **4.9 0.6.1 (2017-12-04)**

- Refactors and optimizations (#686, #632, #684, #636, #631, #629, #635, #683)
- Travis tests for Django 2.0.x (#691)

## **4.10 0.6.0 (2017-11-23)**

- Refactor import\_row call by using keyword arguments (#585)
- Added {{ block.super }} call in block bodyclass in admin/base\_site.html (#582)
- Add support for the Django DurationField with DurationWidget (#575)
- GitHub bmihelac -> django-import-export Account Update (#574)
- Add intersphinx links to documentation (#572)
- Add Resource.get\_import\_fields() (#569)
- Fixed readme mistake (#568)
- Bugfix/fix m2m widget clean (#515)
- Allow injection of context data for template rendered by import\_action() and export\_action() (#544)
- Bugfix/fix exception in generate\_log\_entries() (#543)
- Process import dataset and result in separate methods (#542)
- Bugfix/fix error in converting exceptions to strings (#526)



- Fix admin integration tests for the new “Import finished...” message, update Czech translations to 100% coverage. (#596)
- Make import form type easier to override (#604)
- Add saves\_null\_values attribute to Field to control whether null values are saved on the object (#611)
- Add Bulgarian translations (#656)
- Add django 1.11 to TravisCI (#621)
- Make Signals code example format correctly in documentation (#553)
- Add Django as requirement to setup.py (#634)
- Update import of reverse for django 2.x (#620)
- Add Django-version classifiers to setup.py’s CLASSIFIERS (#616)
- Some fixes for Django 2.0 (#672)
- Strip whitespace when looking up ManyToMany fields (#668)
- Fix all ResourceWarnings during tests in Python 3.x (#637)
- Remove downloads count badge from README since shields.io no longer supports it for PyPi (#677)
- Add coveralls support and README badge (#678)

## 4.11 0.5.1 (2016-09-29)

- French locale not in pypi (#524)
- Bugfix/fix undefined template variables (#519)

## 4.12 0.5.0 (2016-09-01)

- Hide default value in diff when importing a new instance (#458)
- Append rows to Result object via function call to allow overriding (#462)
- Add get\_resource\_kwargs to allow passing request to resource (#457)
- Expose Django user to get\_export\_data() and export() (#447)
- Add before\_export and after\_export hooks (#449)
- fire events post\_import, post\_export events (#440)
- add **\*\***kwargs to export\_data / create\_dataset
- Add before\_import\_row() and after\_import\_row() (#452)
- Add get\_export\_fields() to Resource to control what fields are exported (#461)
- Control user-visible fields (#466)
- Fix diff for models using ManyRelatedManager
- Handle already cleaned objects (#484)
- Add after\_import\_instance hook (#489)
- Use optimized xlsx reader (#482)

- Adds resource\_class of BookResource (re-adds) in admin docs (#481)
- Require POST method for process\_import() (#478)
- Add SimpleArrayWidget to support use of django.contrib.postgres.fields.ArrayField (#472)
- Add new Diff class (#477)
- Fix #375: add row to widget.clean(), obj to widget.render() (#479)
- Restore transactions for data import (#480)
- Refactor the import-export templates (#496)
- Update doc links to the stable version, update rtd to .io (#507)
- Fixed typo in the Czech translation (#495)

### **4.13 0.4.5 (2016-04-06)**

- Add FloatWidget, use with model fields models.FloatField (#433)
- Fix default values in fields (#431, #364)

Field constructor *default* argument is NOT\_PROVIDED instead of None Field clean method checks value against *Field.empty\_values* [None, '']

### **4.14 0.4.4 (2016-03-22)**

- FIX: No static/ when installed via pip #427
- Add total # of imports and total # of updates to import success msg

### **4.15 0.4.3 (2016-03-08)**

- fix MediaStorage does not respect the read\_mode parameter (#416)
- Reset SQL sequences when new objects are imported (#59)
- Let Resource rollback if import throws exception (#377)
- Fixes error when a single value is stored in m2m relation field (#177)
- Add support for django.db.models.TimeField (#381)

### **4.16 0.4.2 (2015-12-18)**

- add xlsx import support

### **4.17 0.4.1 (2015-12-11)**

- fix for fields with a dyanmic default callable (#360)

## 4.18 0.4.0 (2015-12-02)

- Add Django 1.9 support
- Django 1.4 is not supported (#348)

## 4.19 0.3.1 (2015-11-20)

- FIX: importing csv in python 3

## 4.20 0.3 (2015-11-20)

- FIX: importing csv UnicodeEncodeError introduced in 0.2.9 (#347)

## 4.21 0.2.9 (2015-11-12)

- Allow Field.save() relation following (#344)
- Support default values on fields (and models) (#345)
- m2m widget: allow trailing comma (#343)
- Open csv files as text and not binary (#127)

## 4.22 0.2.8 (2015-07-29)

- use the IntegerWidget for database-fields of type BigIntegerField (#302)
- make datetime timezone aware if USE\_TZ is True (#283).
- Fix 0 is interpreted as None in number widgets (#274)
- add possibility to override tmp storage class (#133, #251)
- better error reporting (#259)

## 4.23 0.2.7 (2015-05-04)

- Django 1.8 compatibility
- add attribute inheritance to Resource (#140)
- make the filename and user available to import\_data (#237)
- Add to\_encoding functionality (#244)
- Call before\_import before creating the instance\_loader - fixes #193

## 4.24 0.2.6 (2014-10-09)

- added use of `get_diff_headers` method into `import.html` template (#158)
- Try to use `OrderedDict` instead of `SortedDict`, which is deprecated in Django 1.7 (#157)
- fixed #105 unicode import
- remove invalid form action “form\_url” #154

## 4.25 0.2.5 (2014-10-04)

- Do not convert numeric types to string (#149)
- implement export as an admin action (#124)

## 4.26 0.2.4 (2014-09-18)

- fix: `get_value` raised attribute error on model method call
- Fixed XLS import on python 3. Optimized loop
- Fixed properly skipping row marked as skipped when importing data from the admin interface.
- Allow `Resource.export` to accept iterables as well as querysets
- Improve error messages
- FIX: Properly handle `NullBooleanField` (#115) - Backward Incompatible Change previously `None` values were handled as `false`

## 4.27 0.2.3 (2014-07-01)

- Add separator and field keyword arguments to `ManyToManyWidget`
- FIX: No support for dates before 1900 (#93)

## 4.28 0.2.2 (2014-04-18)

- `RowResult` now stores exception object rather than it's repr
- Admin integration - add `EntryLog` object for each added/updated/deleted instance

## 4.29 0.2.1 (2014-02-20)

- FIX `import_file_name` form field can be use to access the filesystem (#65)

## 4.30 0.2.0 (2014-01-30)

- Python 3 support

## 4.31 0.1.6 (2014-01-21)

- Additional hooks for customizing the workflow (#61)

## 4.32 0.1.5 (2013-11-29)

- Prevent queryset caching when exporting (#44)
- Allow unchanged rows to be skipped when importing (#30)
- Update tests for Django 1.6 (#57)
- Allow different `ResourceClass` to be used in `ImportExportModelAdmin` (#49)

## 4.33 0.1.4

- Use `field_name` instead of `column_name` for field dehydration, FIX #36
- Handle `OneToOneField`, FIX #17 - Exception when attempting access something on the `related_name`.
- FIX #23 - export filter not working

## 4.34 0.1.3

- Fix packaging
- DB transactions support for importing data

## 4.35 0.1.2

- support for deleting objects during import
- bug fixes
- Allowing a field to be 'dehydrated' with a custom method
- added documentation

## 4.36 0.1.1

- added `ExportForm` to admin integration for choosing export file format
- refactor admin integration to allow better handling of specific formats supported features and better handling of reading text files

- include all available formats in Admin integration
- bugfixes

## **4.37 0.1.0**

- Refactor api

For instructions on how to use the models and mixins in this module, please refer to *Admin integration*.

```
class import_export.admin.ExportActionMixin (*args, **kwargs)
    Mixin with export functionality implemented as an admin action.
```

```
    export_admin_action (request, queryset)
        Exports the selected rows using file_format.
```

```
class import_export.admin.ExportActionModelAdmin (*args, **kwargs)
    Subclass of ModelAdmin with export functionality implemented as an admin action.
```

```
class import_export.admin.ExportMixin
    Export mixin.
```

This is intended to be mixed with `django.contrib.admin.ModelAdmin` <https://docs.djangoproject.com/en/2.1/ref/contrib/admin/#modeladmin-objects>

```
change_list_template = 'admin/import_export/change_list_export.html'
    template for change_list view
```

```
export_template_name = 'admin/import_export/export.html'
    template for export view
```

```
formats = [<class 'import_export.formats.base_formats.CSV'>, <class 'import_export.formats.base_formats.XLSX'>]
    available export formats
```

```
get_export_data (file_format, queryset, *args, **kwargs)
    Returns file_format representation for given queryset.
```

```
get_export_formats ()
    Returns available export formats.
```

```
get_export_queryset (request)
    Returns export queryset.
```

Default implementation respects applied search and filters.

```
get_export_resource_class ()
    Returns ResourceClass to use for export.
```

**has\_export\_permission** (*request*)  
Returns whether a request has export permission.

**resource\_class** = None  
resource class

**to\_encoding** = 'utf-8'  
export data encoding

**class** `import_export.admin.ImportExportActionModelAdmin` (*\*args, \*\*kwargs*)  
Subclass of `ExportActionModelAdmin` with import/export functionality. Export functionality is implemented as an admin action.

**class** `import_export.admin.ImportExportMixin`  
Import and export mixin.

**change\_list\_template** = 'admin/import\_export/change\_list\_import\_export.html'  
template for `change_list` view

**class** `import_export.admin.ImportExportModelAdmin` (*model, admin\_site*)  
Subclass of `ModelAdmin` with import/export functionality.

**class** `import_export.admin.ImportMixin`  
Import mixin.

This is intended to be mixed with `django.contrib.admin.ModelAdmin` <https://docs.djangoproject.com/en/2.1/ref/contrib/admin/#modeladmin-objects>

**change\_list\_template** = 'admin/import\_export/change\_list\_import.html'  
template for `change_list` view

**formats** = [`<class 'import_export.formats.base_formats.CSV'>`, `<class 'import_export.formats.csv_formats.CSV'>`, ...]  
available import formats

**from\_encoding** = 'utf-8'  
import data encoding

**get\_confirm\_import\_form** ()  
Get the form type (class) used to confirm the import.

**get\_form\_kwargs** (*form, \*args, \*\*kwargs*)  
Prepare/returns kwargs for the import form.

To distinguish between import and confirm import forms, the following approach may be used:

```
if isinstance(form, ImportForm): # your code here for the import form kwargs # e.g. update.kwargs({...})
```

```
elif isinstance(form, ConfirmImportForm): # your code here for the confirm import form kwargs # e.g. update.kwargs({...})
```

...

**get\_import\_data\_kwargs** (*request, \*args, \*\*kwargs*)  
Prepare kwargs for `import_data`.

**get\_import\_form** ()  
Get the form type used to read the import format and file.

**get\_import\_formats** ()  
Returns available import formats.

**get\_import\_resource\_class** ()  
Returns `ResourceClass` to use for import.



**get\_import\_resource\_kwargs** (*request*, \*args, \*\*kwargs)

Prepares/returns kwargs used when initializing Resource

**get\_resource\_class** ()

Returns ResourceClass

**has\_import\_permission** (*request*)

Returns whether a request has import permission.

**import\_action** (*request*, \*args, \*\*kwargs)

Perform a dry\_run of the import to make sure the import will not result in errors. If there where no error, save the user uploaded file to a local temp file that will be used by 'process\_import' for the actual import.

**import\_template\_name** = 'admin/import\_export/import.html'

template for import view

**process\_import** (*request*, \*args, \*\*kwargs)

Perform the actual import action (after the user has confirmed the import)

**resource\_class** = None

resource class



## 6.1 Resource

**class** `import_export.resources.Resource`

Resource defines how objects are mapped to their import and export representations and handle importing and exporting data.

**after\_delete\_instance** (*instance, dry\_run*)  
Override to add additional logic. Does nothing by default.

**after\_export** (*queryset, data, \*args, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**after\_import** (*dataset, result, using\_transactions, dry\_run, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**after\_import\_instance** (*instance, new, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**after\_import\_row** (*row, row\_result, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**after\_save\_instance** (*instance, using\_transactions, dry\_run*)  
Override to add additional logic. Does nothing by default.

**before\_delete\_instance** (*instance, dry\_run*)  
Override to add additional logic. Does nothing by default.

**before\_export** (*queryset, \*args, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**before\_import** (*dataset, using\_transactions, dry\_run, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**before\_import\_row** (*row, \*\*kwargs*)  
Override to add additional logic. Does nothing by default.

**before\_save\_instance** (*instance, using\_transactions, dry\_run*)  
 Override to add additional logic. Does nothing by default.

**delete\_instance** (*instance, using\_transactions=True, dry\_run=False*)  
 Calls `instance.delete()` as long as `dry_run` is not set.

**export** (*queryset=None, \*args, \*\*kwargs*)  
 Exports a resource.

**for\_delete** (*row, instance*)  
 Returns `True` if `row` importing should delete instance.  
 Default implementation returns `False`. Override this method to handle deletion.

**classmethod get\_diff\_class** ()  
 Returns the class used to display the diff for an imported instance.

**get\_diff\_headers** ()  
 Diff representation headers.

**classmethod get\_error\_result\_class** ()  
 Returns the class used to store an error resulting from an import.

**get\_field\_name** (*field*)  
 Returns the field name for a given field.

**get\_fields** (*\*\*kwargs*)  
 Returns fields sorted according to `export_order`.

**get\_instance** (*instance\_loader, row*)  
 If all 'import\_id\_fields' are present in the dataset, calls the `InstanceLoader`. Otherwise, returns `None`.

**get\_or\_init\_instance** (*instance\_loader, row*)  
 Either fetches an already existing instance or initializes a new one.

**classmethod get\_result\_class** ()  
 Returns the class used to store the result of an import.

**classmethod get\_row\_result\_class** ()  
 Returns the class used to store the result of a row import.

**import\_data** (*dataset, dry\_run=False, raise\_errors=False, use\_transactions=None, collect\_failed\_rows=False, \*\*kwargs*)  
 Imports data from `tablib.Dataset`. Refer to *Import data workflow* for a more complete description of the whole import process.

#### Parameters

- **dataset** – A `tablib.Dataset`
- **raise\_errors** – Whether errors should be printed to the end user or raised regularly.
- **use\_transactions** – If `True` the import process will be processed inside a transaction.
- **collect\_failed\_rows** – If `True` the import process will collect failed rows.
- **dry\_run** – If `dry_run` is set, or an error occurs, if a transaction is being used, it will be rolled back.

**import\_field** (*field, obj, data, is\_m2m=False*)  
 Calls `import_export.fields.Field.save()` if `Field.attribute` and `Field.column_name` are found in `data`.

**import\_obj** (*obj, data, dry\_run*)

Traverses every field in this Resource and calls `import_field()`. If `import_field()` results in a `ValueError` being raised for one of more fields, those errors are captured and re-raised as a single, multi-field `ValidationError`.

**import\_row** (*row, instance\_loader, using\_transactions=True, dry\_run=False, \*\*kwargs*)

Imports data from `tablib.Dataset`. Refer to [Import data workflow](#) for a more complete description of the whole import process.

#### Parameters

- **row** – A dict of the row to import
- **instance\_loader** – The instance loader to be used to load the row
- **using\_transactions** – If `using_transactions` is set, a transaction is being used to wrap the import
- **dry\_run** – If `dry_run` is set, or error occurs, transaction will be rolled back.

**save\_instance** (*instance, using\_transactions=True, dry\_run=False*)

Takes care of saving the object to the database.

Keep in mind that this is done by calling `instance.save()`, so objects are not created in bulk!

**save\_m2m** (*obj, data, using\_transactions, dry\_run*)

Saves m2m fields.

Model instance need to have a primary key value before a many-to-many relationship can be used.

**skip\_row** (*instance, original*)

Returns `True` if row importing should be skipped.

Default implementation returns `False` unless `skip_unchanged == True`. Override this method to handle skipping rows meeting certain conditions.

Use `super` if you want to preserve default handling while overriding

```
class YourResource(ModelResource):
    def skip_row(self, instance, original):
        # Add code here
        return super(YourResource, self).skip_row(instance, original)
```

**validate\_instance** (*instance, import\_validation\_errors=None, validate\_unique=True*)

Takes any validation errors that were raised by `import_obj()`, and combines them with validation errors raised by the instance's `full_clean()` method. The combined errors are then re-raised as single, multi-field `ValidationError`.

If the `clean_model_instances` option is `False`, the instances's `full_clean()` method is not called, and only the errors raised by `import_obj()` are re-raised.

## 6.2 ModelResource

**class** `import_export.resources.ModelResource`

`ModelResource` is `Resource` subclass for handling Django models.

**DEFAULT\_RESOURCE\_FIELD**

alias of `import_export.fields.Field`

**after\_import** (*dataset, result, using\_transactions, dry\_run, \*\*kwargs*)

Reset the SQL sequences after new objects are imported

**classmethod** `field_from_django_field` (*field\_name*, *django\_field*, *readonly*)

Returns a Resource Field instance for the given Django model field.

**classmethod** `get_fk_widget` (*field*)

Prepare widget for fk and o2o fields

**get\_import\_id\_fields** ()

**classmethod** `get_m2m_widget` (*field*)

Prepare widget for m2m field

**get\_queryset** ()

Returns a queryset of all objects for this model. Override this if you want to limit the returned queryset.

**init\_instance** (*row=None*)

Initializes a new Django model.

**classmethod** `widget_from_django_field` (*f*, *default=<class 'import-export.widgets.Widget'>*)

Returns the widget that would likely be associated with each Django type.

Includes mapping of Postgres Array and JSON fields. In the case that psycopg2 is not installed, we consume the error and process the field regardless.

**classmethod** `widget_kwargs_for_field` (*field\_name*)

Returns widget kwargs for given field\_name.

## 6.3 ResourceOptions (Meta)

**class** `import_export.resources.ResourceOptions`

The inner Meta class allows for class-level configuration of how the Resource should behave. The following options are available:

**clean\_model\_instances = False**

Controls whether `instance.full_clean()` is called during the import process to identify potential validation errors for each (non skipped) row. The default value is False.

**exclude = None**

Controls what introspected fields the Resource should NOT include. A blacklist of fields.

**export\_order = None**

Controls export order for columns.

**fields = None**

Controls what introspected fields the Resource should include. A whitelist of fields.

**import\_id\_fields = ['id']**

Controls which object fields will be used to identify existing instances.

**instance\_loader\_class = None**

Controls which class instance will take care of loading existing objects.

**model = None**

Django Model class. It is used to introspect available fields.

**report\_skipped = True**

Controls if the result reports skipped rows Default value is True

**skip\_unchanged = False**

Controls if the import should skip unchanged records. Default value is False

**use\_transactions = None**

Controls if import should use database transactions. Default value is None meaning settings.  
IMPORT\_EXPORT\_USE\_TRANSACTIONS will be evaluated.

**widgets = None**

This dictionary defines widget kwargs for fields.

## 6.4 modelresource\_factory

`resources.modelresource_factory` (*resource\_class=<class 'import\_export.resources.ModelResource'>*)  
Factory for creating `ModelResource` class for given Django model.





**class** `import_export.widgets.Widget`

A `Widget` takes care of converting between import and export representations.

This is achieved by the two methods, `clean()` and `render()`.

**clean** (*value*, *row=None*, \**args*, \*\**kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.IntegerWidget`

Widget for converting integer fields.

**clean** (*value*, *row=None*, \**args*, \*\**kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**class** `import_export.widgets.DecimalWidget`

Widget for converting decimal fields.

**clean** (*value*, *row=None*, \**args*, \*\**kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**class** `import_export.widgets.CharWidget`

Widget for converting text fields.

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.BooleanWidget`

Widget for converting boolean fields.

**clean** (*value*, *row=None*, *\*args*, *\*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.DateWidget` (*format=None*)

Widget for converting date fields.

Takes optional `format` parameter.

**clean** (*value*, *row=None*, *\*args*, *\*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.TimeWidget` (*format=None*)

Widget for converting time fields.

Takes optional `format` parameter.

**clean** (*value*, *row=None*, *\*args*, *\*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.DateTimeWidget` (*format=None*)

Widget for converting date fields.

Takes optional `format` parameter. If none is set, either `settings.DATETIME_INPUT_FORMATS` or `"%Y-%m-%d %H:%M:%S"` is used.

**clean** (*value, row=None, \*args, \*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value, obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.DurationWidget`

Widget for converting time duration fields.

**clean** (*value, row=None, \*args, \*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value, obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.JSONWidget`

Widget for a JSON object (especially required for jsonb fields in PostgreSQL database.)

**Parameters** `value` – Defaults to JSON format.

The widget covers two cases: Proper JSON string with double quotes, else it tries to use single quotes and then convert it to proper JSON.

**clean** (*value, row=None, \*args, \*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value, obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.ForeignKeyWidget` (*model, field='pk', \*args, \*\*kwargs*)

Widget for a ForeignKey field which looks up a related model using "natural keys" in both export an import.

The lookup field defaults to using the primary key (pk) as lookup criterion but can be customised to use any field on the related model.

Unlike specifying a related field in your resource like so...

```
class Meta:
    fields = ('author__name',)
```

...using a *ForeignKeyWidget* has the advantage that it can not only be used for exporting, but also importing data with foreign key relationships.

Here's an example on how to use *ForeignKeyWidget* to lookup related objects using `Author.name` instead of `Author.pk`:

```
from import_export import fields, resources
from import_export.widgets import ForeignKeyWidget

class BookResource(resources.ModelResource):
    author = fields.Field(
        column_name='author',
        attribute='author',
        widget=ForeignKeyWidget(Author, 'name'))

class Meta:
    fields = ('author',)
```

### Parameters

- **model** – The Model the ForeignKey refers to (required).
- **field** – A field on the related model used for looking up a particular object.

**clean** (*value*, *row=None*, *\*args*, *\*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, *clean()* handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**get\_queryset** (*value*, *row*, *\*args*, *\*\*kwargs*)

Returns a queryset of all objects for this Model.

Overwrite this method if you want to limit the pool of objects from which the related object is retrieved.

### Parameters

- **value** – The field's value in the datasource.
- **row** – The datasource's current row.

As an example; if you'd like to have *ForeignKeyWidget* look up a Person by their pre- **and** lastname column, you could subclass the widget like so:

```
class FullNameForeignKeyWidget(ForeignKeyWidget):
    def get_queryset(self, value, row):
        return self.model.objects.filter(
            first_name__iexact=row["first_name"],
            last_name__iexact=row["last_name"]
        )
```

**render** (*value*, *obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.

**class** `import_export.widgets.ManyToManyWidget` (*model, separator=None, field=None, \*args, \*\*kwargs*)

Widget that converts between representations of a ManyToMany relationships as a list and an actual ManyToMany field.

#### Parameters

- **model** – The model the ManyToMany field refers to (required).
- **separator** – Defaults to ', '.
- **field** – A field on the related model. Default is pk.

**clean** (*value, row=None, \*args, \*\*kwargs*)

Returns an appropriate Python object for an imported value.

For example, if you import a value from a spreadsheet, `clean()` handles conversion of this value into the corresponding Python object.

Numbers or dates can be *cleaned* to their respective data types and don't have to be imported as Strings.

**render** (*value, obj=None*)

Returns an export representation of a Python value.

For example, if you have an object you want to export, `render()` takes care of converting the object's field to a value that can be written to a spreadsheet.



```
class import_export.fields.Field(attribute=None, column_name=None, widget=None, default=<class 'django.db.models.fields.NOT_PROVIDED'>, readonly=False, saves_null_values=True)
```

Field represent mapping between *object* field and representation of this field.

#### Parameters

- **attribute** – A string of either an instance attribute or callable off the object.
- **column\_name** – Lets you provide a name for the column that represents this field in the export.
- **widget** – Defines a widget that will be used to represent this field’s data in the export.
- **readonly** – A Boolean which defines if this field will be ignored during import.
- **default** – This value will be returned by `clean()` if this field’s widget did not return an adequate value.
- **saves\_null\_values** – Controls whether null values are saved on the object

**clean** (*data*)

Translates the value stored in the imported datasource to an appropriate Python object and returns it.

**export** (*obj*)

Returns value from the provided object converted to export representation.

**get\_value** (*obj*)

Returns the value of the object’s attribute.

**save** (*obj, data, is\_m2m=False*)

If this field is not declared readonly, the object’s attribute will be set to the value returned by `clean()`.





---

### Instance loaders

---

**class** `import_export.instance_loaders.BaseInstanceLoader` (*resource, dataset=None*)  
Base abstract implementation of instance loader.

**class** `import_export.instance_loaders.ModelInstanceLoader` (*resource, dataset=None*)  
Instance loader for Django model.

Lookup for model instance by `import_id_fields`.

**class** `import_export.instance_loaders.CachedInstanceLoader` (*\*args, \*\*kwargs*)  
Loads all possible model instances in dataset avoid hitting database for every `get_instance` call.

This instance loader work only when there is one `import_id_fields` field.



### 10.1 TempFolderStorage

```
class import_export.tmp_storages.TempFolderStorage (name=None)
```

### 10.2 CacheStorage

```
class import_export.tmp_storages.CacheStorage (name=None)  
    By default memcache maximum size per key is 1MB, be careful with large files.
```

### 10.3 MediaStorage

```
class import_export.tmp_storages.MediaStorage (name=None)
```



### 11.1 Result

```
class import_export.results.Result(*args, **kwargs)
```

```
    has_errors()
```

Returns a boolean indicating whether the import process resulted in any critical (non-validation) errors for this result.

```
    has_validation_errors()
```

Returns a boolean indicating whether the import process resulted in any validation errors for this result.



```
class import_export.forms.ImportForm(import_formats, *args, **kwargs)
class import_export.forms.ConfirmImportForm(data=None, files=None,
auto_id='id_%s', prefix=None, initial=None, error_class=<class
'django.forms.utils.ErrorList'>,
label_suffix=None,
empty_permitted=False, field_order=None,
use_required_attribute=None, renderer=None)
```





i

`import_export.admin`, 27  
`import_export.forms`, 51  
`import_export.instance_loaders`, 45



## A

after\_delete\_instance() (import\_export.resources.Resource method), 31

after\_export() (import\_export.resources.Resource method), 31

after\_import() (import\_export.resources.ModelResource method), 33

after\_import() (import\_export.resources.Resource method), 31

after\_import\_instance() (import\_export.resources.Resource method), 31

after\_import\_row() (import\_export.resources.Resource method), 31

after\_save\_instance() (import\_export.resources.Resource method), 31

## B

BaseInstanceLoader (class in import\_export.instance\_loaders), 45

before\_delete\_instance() (import\_export.resources.Resource method), 31

before\_export() (import\_export.resources.Resource method), 31

before\_import() (import\_export.resources.Resource method), 31

before\_import\_row() (import\_export.resources.Resource method), 31

before\_save\_instance() (import\_export.resources.Resource method), 31

BooleanWidget (class in import\_export.widgets), 38

## C

CachedInstanceLoader (class in import\_export.instance\_loaders), 45

CacheStorage (class in import\_export.tmp\_storages), 47

change\_list\_template (import\_export.admin.ExportMixin attribute), 27

change\_list\_template (import\_export.admin.ImportExportMixin attribute), 28

change\_list\_template (import\_export.admin.ImportMixin attribute), 28

CharWidget (class in import\_export.widgets), 38

clean() (import\_export.fields.Field method), 43

clean() (import\_export.widgets.BooleanWidget method), 38

clean() (import\_export.widgets.DateTimeWidget method), 39

clean() (import\_export.widgets.DateWidget method), 38

clean() (import\_export.widgets.DecimalWidget method), 37

clean() (import\_export.widgets.DurationWidget method), 39

clean() (import\_export.widgets.ForeignKeyWidget method), 40

clean() (import\_export.widgets.IntegerWidget method), 37

clean() (import\_export.widgets.JSONWidget method), 39

clean() (import\_export.widgets.ManyToManyWidget method), 41

clean() (import\_export.widgets.TimeWidget method), 38

clean() (import\_export.widgets.Widget method), 37

`clean_model_instances` (*import\_export.resources.ResourceOptions* attribute), 34

`ConfirmImportForm` (*class in import\_export.forms*), 51

## D

`DateTimeWidget` (*class in import\_export.widgets*), 38

`DateWidget` (*class in import\_export.widgets*), 38

`DecimalWidget` (*class in import\_export.widgets*), 37

`DEFAULT_RESOURCE_FIELD` (*import\_export.resources.ModelResource* attribute), 33

`delete_instance()` (*import\_export.resources.Resource* method), 32

`DurationWidget` (*class in import\_export.widgets*), 39

## E

`exclude` (*import\_export.resources.ResourceOptions* attribute), 34

`export()` (*import\_export.fields.Field* method), 43

`export()` (*import\_export.resources.Resource* method), 32

`export_admin_action()` (*import\_export.admin.ExportActionMixin* method), 27

`export_order` (*import\_export.resources.ResourceOptions* attribute), 34

`export_template_name` (*import\_export.admin.ExportMixin* attribute), 27

`ExportActionMixin` (*class in import\_export.admin*), 27

`ExportActionModelAdmin` (*class in import\_export.admin*), 27

`ExportMixin` (*class in import\_export.admin*), 27

## F

`Field` (*class in import\_export.fields*), 43

`field_from_django_field()` (*import\_export.resources.ModelResource* class method), 33

`fields` (*import\_export.resources.ResourceOptions* attribute), 34

`for_delete()` (*import\_export.resources.Resource* method), 32

`ForeignKeyWidget` (*class in import\_export.widgets*), 39

`formats` (*import\_export.admin.ExportMixin* attribute), 27

`formats` (*import\_export.admin.ImportMixin* attribute), 28

`from_encoding` (*import\_export.admin.ImportMixin* attribute), 28

## G

`get_confirm_import_form()` (*import\_export.admin.ImportMixin* method), 28

`get_diff_class()` (*import\_export.resources.Resource* class method), 32

`get_diff_headers()` (*import\_export.resources.Resource* method), 32

`get_error_result_class()` (*import\_export.resources.Resource* class method), 32

`get_export_data()` (*import\_export.admin.ExportMixin* method), 27

`get_export_formats()` (*import\_export.admin.ExportMixin* method), 27

`get_export_queryset()` (*import\_export.admin.ExportMixin* method), 27

`get_export_resource_class()` (*import\_export.admin.ExportMixin* method), 27

`get_field_name()` (*import\_export.resources.Resource* method), 32

`get_fields()` (*import\_export.resources.Resource* method), 32

`get_fk_widget()` (*import\_export.resources.ModelResource* class method), 34

`get_form_kwargs()` (*import\_export.admin.ImportMixin* method), 28

`get_import_data_kwargs()` (*import\_export.admin.ImportMixin* method), 28

`get_import_form()` (*import\_export.admin.ImportMixin* method), 28

`get_import_formats()` (*import\_export.admin.ImportMixin* method), 28

`get_import_id_fields()` (*import\_export.resources.ModelResource* method), 34

`get_import_resource_class()` (*import\_export.admin.ImportMixin* method), 28

[get\\_import\\_resource\\_kwargs\(\)](#) (*import\_export.admin.ImportMixin* method), 28  
[get\\_instance\(\)](#) (*import\_export.resources.Resource* method), 32  
[get\\_m2m\\_widget\(\)](#) (*import\_export.resources.ModelResource* class method), 34  
[get\\_or\\_init\\_instance\(\)](#) (*import\_export.resources.Resource* method), 32  
[get\\_queryset\(\)](#) (*import\_export.resources.ModelResource* method), 34  
[get\\_queryset\(\)](#) (*import\_export.widgets.ForeignKeyWidget* method), 40  
[get\\_resource\\_class\(\)](#) (*import\_export.admin.ImportMixin* method), 29  
[get\\_result\\_class\(\)](#) (*import\_export.resources.Resource* class method), 32  
[get\\_row\\_result\\_class\(\)](#) (*import\_export.resources.Resource* class method), 32  
[get\\_value\(\)](#) (*import\_export.fields.Field* method), 43

**H**

[has\\_errors\(\)](#) (*import\_export.results.Result* method), 49  
[has\\_export\\_permission\(\)](#) (*import\_export.admin.ExportMixin* method), 28  
[has\\_import\\_permission\(\)](#) (*import\_export.admin.ImportMixin* method), 29  
[has\\_validation\\_errors\(\)](#) (*import\_export.results.Result* method), 49

**I**

[import\\_action\(\)](#) (*import\_export.admin.ImportMixin* method), 29  
[import\\_data\(\)](#) (*built-in function*), 15  
[import\\_data\(\)](#) (*import\_export.resources.Resource* method), 32  
[import\\_export.admin](#) (*module*), 27  
[import\\_export.forms](#) (*module*), 51  
[import\\_export.instance\\_loaders](#) (*module*), 45  
[import\\_field\(\)](#) (*import\_export.resources.Resource* method), 32

[import\\_id\\_fields](#) (*import\_export.resources.ResourceOptions* attribute), 34  
[import\\_obj\(\)](#) (*import\_export.resources.Resource* method), 32  
[import\\_row\(\)](#) (*import\_export.resources.Resource* method), 33  
[import\\_template\\_name](#) (*import\_export.admin.ImportMixin* attribute), 29  
[ImportExportActionModelAdmin](#) (*class in import\_export.admin*), 28  
[ImportExportMixin](#) (*class in import\_export.admin*), 28  
[ImportExportModelAdmin](#) (*class in import\_export.admin*), 28  
[ImportForm](#) (*class in import\_export.forms*), 51  
[ImportMixin](#) (*class in import\_export.admin*), 28  
[init\\_instance\(\)](#) (*import\_export.resources.ModelResource* method), 34  
[instance\\_loader\\_class](#) (*import\_export.resources.ResourceOptions* attribute), 34  
[IntegerWidget](#) (*class in import\_export.widgets*), 37

**J**

[JSONWidget](#) (*class in import\_export.widgets*), 39

**M**

[ManyToManyWidget](#) (*class in import\_export.widgets*), 41  
[MediaStorage](#) (*class in import\_export.tmp\_storages*), 47  
[model](#) (*import\_export.resources.ResourceOptions* attribute), 34  
[ModelInstanceLoader](#) (*class in import\_export.instance\_loaders*), 45  
[ModelResource](#) (*class in import\_export.resources*), 33  
[modelresource\\_factory\(\)](#) (*import\_export.resources* method), 35

**P**

[process\\_import\(\)](#) (*import\_export.admin.ImportMixin* method), 29

**R**

[render\(\)](#) (*import\_export.widgets.BooleanWidget* method), 38  
[render\(\)](#) (*import\_export.widgets.CharWidget* method), 38

render() (*import\_export.widgets.DateTimeWidget method*), 39

render() (*import\_export.widgets.DateWidget method*), 38

render() (*import\_export.widgets.DurationWidget method*), 39

render() (*import\_export.widgets.ForeignKeyWidget method*), 40

render() (*import\_export.widgets.JSONWidget method*), 39

render() (*import\_export.widgets.ManyToManyWidget method*), 41

render() (*import\_export.widgets.TimeWidget method*), 38

render() (*import\_export.widgets.Widget method*), 37

report\_skipped (*import\_export.resources.ResourceOptions attribute*), 34

Resource (*class in import\_export.resources*), 31

resource\_class (*import\_export.admin.ExportMixin attribute*), 28

resource\_class (*import\_export.admin.ImportMixin attribute*), 29

ResourceOptions (*class in import\_export.resources*), 34

Result (*class in import\_export.results*), 49

## S

save() (*import\_export.fields.Field method*), 43

save\_instance() (*import\_export.resources.Resource method*), 33

save\_m2m() (*import\_export.resources.Resource method*), 33

skip\_row() (*import\_export.resources.Resource method*), 33

skip\_unchanged (*import\_export.resources.ResourceOptions attribute*), 34

## T

TempFolderStorage (*class in import\_export.tmp\_storages*), 47

TimeWidget (*class in import\_export.widgets*), 38

to\_encoding (*import\_export.admin.ExportMixin attribute*), 28

## U

use\_transactions (*import\_export.resources.ResourceOptions attribute*), 34

## V

validate\_instance() (*im-*

## W

Widget (*class in import\_export.widgets*), 37

widget\_from\_django\_field() (*import\_export.resources.ModelResource class method*), 34

widget\_kwargs\_for\_field() (*import\_export.resources.ModelResource class method*), 34

widgets (*import\_export.resources.ResourceOptions attribute*), 35